



ANTICOR

RUST-PREVENTING AGENT AND PRIMER

PRODUCT DESCRIPTION

Anticor – rust-preventing agent and primer 2 in 1. The product retards and neutralizes corrosion, forming a protective precoat for post processing.

The material dries quickly, is easy to use, resistant to solvents.

The material can be applied over corroded surfaces after removing weakly adjacent rust.

PHYSICAL AND CHEMICAL PROPERTIES

Color:	beige
Odor:	slight odor
Density:	1.02 g/cm ³
Volume:	100ml, 250ml
Drying time:	6-8 hours at 200°C and relative humidity 50%
Spreading rate:	2m ² /100 ml
pH value:	1.50

VOLATILE ORGANIC COMPOUNDS

The product does not contain VOC.

APPLICATION

- Remove contaminants and weakly adjacent rust from the damaged area using metal fiber brush. Treat the surface with solvent or degreaser.
- Shake well before using.
- Spread the primer evenly on the corroded area.
- 3-4 coatings are recommended depending on degree of corrosion.
- Before further processing the user should wait until the end of reaction, when the surface is black and blue.
- Dry treated surface can be over coated with primer or paint.

It is recommended to apply the product in good ventilated rooms or outdoors.

CAUTION! To maintain safety, always follow the instructions given in the MSDS for the product.

STORAGE

The product must be stored in dry well ventilated rooms at 10-25°C and relative humidity max. 60%